

Baulängen nach ANSI B16.10
Face to face dimensions acc. ANSI B16.10

A - Absperrschieber

A - Gate Valve

B - Absperrventil

B - Globe Valve

C - Rückschlagklappe

C - Swing Check Valve

Typ/Type		A Gate Valve			B Globe Valve			C Check Valve		
Class		150	300	600	150	300	600	150	300	600
DN/Size		Baulänge in mm / f.t.f. dimensions in mm.								
50	2"	178	216	292	203	267	292	203	267	292
80	3"	203	283	356	241	318	356	241	318	356
100	4"	229	305	432	292	356	432	292	356	432
150	6"	267	403	559	406	445	559	356	445	559
200	8"	292	419	660	495	559	660	495	533	660
250	10"	330	457	787	622	622	787	622	622	787
300	12"	356	502	838	699	711	838	699	711	838
350	14"	381	762	889				788	838	889
400	16"	406	838	991				864	864	991
450	18"	432	914	1082				978	978	1092
500	20"	457	991	1194				978	1016	1194
550	22"	508								
600	24"	508	1143	1397				1295	1346	1397
650	26"	559								
700	28"	610	1346					1448		
750	30"	610	1397	1651				1524		
800	32"	660								
850	34"	711								
900	36"	711	1727	2083				1956		